

Hologram NFC Epoxy Tag



Quick Details

Leadercolor LDF-D30E RFID Tag is produced with Solid color background with shiny logo and shiny Sparkling hologram background, it can OEM with customzied design, each RFID chip has a unique ID code, in which high frequency and ultra high frequency chips can also be written according to customer needs. Based on the characteristics of RFID, which is widely used for school, bank, super market etc. Mangement.

Description

| RFID Parameter | |
|--------------------|-------------------------------|
| Model No. | LDF-D30E |
| Type | HF RFID Epoxy Tag |
| Protocol | ISO / IEC 14443 A & 18000-3 |
| Frequency | Worldwide HF 13.56Mhz |
| Chip | Compatible MIFARE Classic® 1K |
| Memory | UID 4/7Byte User 1K Byte |
| Read&Write | Supported |
| Read Range | 0.1-10cm |
| Data retention | 10years |
| Programming Cycles | 100,000 cycles |
| Physical Parameter | |
| Size | Dia30mm / 1.18inch; |
| Substrate Material | PVC and Epoxy+shiny hologram |
| Antenna Material | Aluminum Etching |
| Surface Material | PVC waterproof |
| Encode | Supported |
| Installation | Single or Self adhesive |

| | |
|-----------------------|---|
| Operating temperature | 1>Recommended: -25°C to +60°C 2> Operating Temp: -20°C to +80°C |
| Package | Single pack |
| Customized Service | Optional Chips: MIFARE® Series, NTAG® Series Optional Materials: Coated Paper; PVC Paper; Synthetic PP Paper; PET Paper; Optional Glues: Standard Glues; 3M Glues; Strong Glues; Optional Printing: Offset Printing; Barcode Printing; UID Number Printing; UV Printing Optional Crafts: UID encoding; Optional Sizes: Smaller or Bigger |

Application

- NFC posters, NFC device data connection and data transmission
- Mobile payment, Mobile wallet
- Product identification, personnel identification management
- E-ticketing, Loyalty System, Marketing and Advertisements