


SPECIFICATION



Product name: UHF Anti-metal Sticker

Item NO.: LDR-6025M

Version: V1.0

Date: 2020.12.15

Tel: +86-755-89379391 Fax: +86-755-89379456 E-mail: sales@leadercolor.com www.leadercolor.com Add: 2F, Building A11, No.6 Xinfeng Road, Taizhong Industrial Zone, Longgang District, Shenzhen China 518172







LDR-6025M Printable UHF Anti-metal Tag is our self-designed and self-developed tag which is suitable for asset management and metal objects of air cylinder and pipes etc.. With special anti-metal material and Monza chip, its read range up to 6meters when it pastes on the metal surface. It supports printing on RFID printer by rolls.

RFID Parameter


Model No.	LDR-6025M
Туре	Passive UHF RFID Tag
Protocol	ISO/IEC 18000-6C, EPC Class1 Gen2
Frequency	EU Standard 865-868mhz, US Standard 902-928mhz
Chip	Impinj Monza MR6-P
Memory	EPC: 128bits
	Unique TID: 48bits
	User: 32bits
Read&Write	Supported
Read Range	Max. 0.45meter
Data retention	10years
Programming Cycles	100,000 cycles
Anti-collision	Support multiple tags reading



Physical Parameter -


Size	60×25×1.26mm
Substrate Material	Transparent Release Film
Antenna Material	PET+ Etched Alumium
Surface Material	PET Waterproof (Thermal or Transfer Optional)
Tamper Proof	Yes
Encode	Supported
Installation	Self adhesive
Operating Temperature	-40℃ ~ +85℃
Operating Humidity	20% ~ 90%RH, Non-condensing
Package	500pcs/roll
Remark	When it pastes on curving objects, the read range will be shorted by half.
Roll Diameter	Inner size: 3 inches (76.2 mm)/Outter size: 8 inches (203 mm)

US Standard -







EU Standard



Structure -







Application

- 1. Item level management;
- 2. RFID Asset tracking management;
- 3. Hospital equipment management;
- 4. Metal devices supply chain management;

