

Desktop ISO14443A Protocol HF Tag Reader



Model: LDF-1036USB

Size: 105mmx70mmx11mm

Weight: 80g

GENERAL DESCRIPTION

Page1 Total2

Shenzhen Leadercolor Smart Card Co., Ltd.

Add: 2F, Building A11, No.6 Xinfeng Road, Taizhong Industrial Zone, Longgang District, Shenzhen China

Tel: +86 755 89379391 89379456

Fax: +86 755 89379456

www.leadercolor.com

E-Mail: sales@leadercolor.com

LDF-1036USB is a high performance ISO14443A Protocol HF tag reader. It is designed upon fully self-intellectual property and supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as logistics, personnel identification, conference attendance system, access control, anti-counterfeit and industrial production process control system.

FEATURES

- Self-intellectual property;
- Support mainstream ISO14443A protocol tag;
- Advanced tag processing algorithm, high identification rate;
- Built-in TX/RX antenna with effective distance up to 150mm *;
- Low power dissipation design;
- USB 1.1 interface. No external power source needed;
- Provide DLL and demonstration software to facilitate development.

CHARACTERISTICS

- Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	6	V
Operating Temp.	T _{OPR}	-10~+60	°C
Storage Temp.	T _{STR}	-25~+80	°C

- Electrical and Mechanical Specification

Under T_A=25°C, VCC=+5V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	3.3	5	5.5	V
Current Dissipation	I _c		90	150	mA
Frequency	F _{REQ}		13.56		MHz
Effective Distance*	DIS	0	100	150	mm

*Effective distance depends on tag and working environment.

Remark:

1. Specifications are subject to change, please pay attention to our latest one.
2. Shenzhen Leadercolor Smart Ccard Co., Ltd. reserves the right to the final interpretation of the above terms.