

## Dual Protocol HF Tag Reader



**Model: LDF-7036SRIP**

**Size: 123mmx94mmx29mm**

**Weight: 144g**

## GENERAL DESCRIPTION


LDF-7036SRIP is a high performance Dual Protocol HF tag reader supporting ISO/IEC15693, ISO14443TypeA/TypeB. It is designed upon fully self-intellectual property and supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as personnel identification, conference attendance system, access control, anti-counterfeit and industrial production process control system.

## FEATURES

- ✓ Support mainstream ISO/IEC15693, ISO14443TypeA/TypeB protocol tag (TI, PHILIPS, ST, INFINEON, FUJITSU, EM...);
- ✓ Advanced tag processing algorithm, high identification rate;
- ✓ Built-in TX/RX antenna with effective distance up to 100mm \*;
- ✓ Support Transparent Command operation①;
- ✓ Low power dissipation design with single DC+12V power source needed;
- ✓ Support TCP/IP and RS232 interface and provide DLL and demonstration software to facilitate development;
- ✓ Provide DLL and demonstration software to facilitate development.

①Transparent Command Operation: It is an advanced feature designed to support tag's future functions and different chip vendors' customized tag functions.

## INTERFACE



## CHARACTERISTICS

### ● Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	12	V
Operating Temp.	T <sub>OPR</sub>	-10~+60	°C
Storage Temp.	T <sub>STR</sub>	-25~+80	°C

### ● Electrical and Mechanical Specification

Under  $T_A=25^{\circ}\text{C}$ ,  $V_{CC}=+12\text{V}$  unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	11.5	12	15	V
Current Dissipation	Ic		150	200	mA
Frequency	FREQ		13.56		MHz
Effective Distance*	DIS	0	80	100	mm

\*Effective distance depends on tag and working environment.

Remark: 1. Specifications are subject to change, please pay attention to our latest one.

2. Leadercolor reserves the right to the final interpretation of the above terms.